

# Magic Mud Taping Compound

## Description

Magic Mud is a polymer based, extremely elastomeric drywall texturing, joint bridging and leveling compound for interior use.

## Color

Beige

## Container

50 pounds net weight / 5-gallon pail

## Use

Magic Mud is used at seams, inside and outside corners on interior drywall for applications where traditional drywall taping compounds would normally crack.

## Adhesion

Excellent adhesion to gypsum and cement board sheathing.

## Coverage

Approximately 500 square feet of wall board per 5 gallon pail, assuming 4'x8' sheathing dimensions.

## Drying Time

1-4 hours, depending on climate. Drying time can be greatly affected by temperature and humidity.

## Storage

Protect from freezing. Store in a cool, dry area tightly sealed. Recommended storage temperature between 40-90°F.

## Clean-up

Water soluble when wet.

## Shelf Life

One year, if protected from direct sunlight and freezing temperatures.

## Limitations

1. Ambient and surface temperatures must be above 40°F during application and drying period.
2. Magic Mud should only be used for interior applications.

## Surface Preparation

Substrate must be clean, dry, and free from all loose or foreign materials prior to application of Magic Mud.

## Application

Magic Mud is applied to the substrate using the same tools and techniques as standard drywall compound. However, because of the high Acrylic Polymer content and its elastomeric characteristics, this is not a product that can be sanded. Therefore, it is recommended that you do not crown seams or joints to be sanded smooth later.