

SAFETY DATA SHEET

SECTION 1 : IDENTIFICATION

Product identifier used on the label:

Product Name: Euroseal

Other means of identification:

Synonyms: 100% Acrylic Polymer Antiquing Sealer

Recommended use of the chemical and restrictions on use:

 $\underline{\textbf{Chemical manufacturer address and telephone number:}}$

Stuc-O-flex International, Inc Manufacturer Name:

Address: 17635 NE 67th Court Redmond, WA 98052

USA

Website: www.stucoflex.com General Phone Number: 800-305-1045 425-869-0107 General Fax Number: 425-885-5085 Customer Service Phone Number: Technical Product Information: 425-885-5085

Emergency phone number:

Emergency Phone Number: CHEMTREC 1-800-424-9300

SECTION 2: HAZARD(S) IDENTIFICATION

 $\underline{\hbox{Classification of the chemical in accordance with CFR 1910.1200(d)(f):}\\$

GHS Pictograms:

Signal Word: WARNING!

GHS Class: Skin Irritant, Category 3.

Eye Irritant, Category 2B. Hazardous to the aquatic environment.

Hazard Statements: H315 - Causes skin irritation. H320 - Causes eye irritation.

H402 - Harmful to aquatic life.

Precautionary Statements: P261 - Avoid breathing dust/fumes/gas/mist/vapors/spray.

P273 - Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 - In On Skin: Wash with plenty of water.

P333+P313 - If slin irritation or rash occurs; get medical advice/attention.

P362+P364 - Take off contaminated clothing and wash before reuse.

P501 - Dispose of content/container in accordance with Local, State, Federal and Provincial regulations.

Hazards not otherwise classified that have been identified during the classification process:

Potential Health Effects:

Eve: Causes eye irritation. Skin: Causes skin irritation.

Inhalation: $\label{prolonged} \mbox{ Prolonged or excessive inhalation may cause respiratory tract irritation.}$

Ingestion: May be harmful if swallowed.

Chronic Health Effects: Prolonged or repeated contact may cause skin irritation. Signs/Symptoms: Overexposure may cause headaches and dizziness.

Target Organs: Eyes. Skin. Respiratory system. Digestive system.

Aggravation of Pre-Existing

None generally recognized.

Euroseal Product Code: NC-Template Revision:: 5/23/2019

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures:

Chemical Name	CAS#	Ingredient Percent	EC Num.
Non hazardous	No Data	2 - 3 by weight	
Proprietary polymer*	No Data	20 - 30 by weight	
Water	7732-18-5	65 - 75 by weight	231-791-2
Alcohols, C9-11, ethoxylated	68439-46-3	0.05 - 0.10 by weight	614-482-0
Diuron	330-54-1	0.1 - 0.5 by weight	330-54-1
Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	41556-26-7	0.1 - 0.5 by weight	255-437-1
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	0.1 - 0.5 by weight	265-169-7

SECTION 4: FIRST AID MEASURES

Description of necessary measures:

Skin Contact:

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of

the eyes by separating the eyelids with fingers. Remove contacts if present and easy to do. Continue rinsing. Get medical attention, if irritation or symptoms of overexposure persists.

Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained

personnel. Seek immediate medical attention

Ingestion: If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give

anything by mouth to an unconscious person

SECTION 5: FIRE FIGHTING MEASURES

Suitable and unsuitable extinguishing media:

Suitable Extinguishing Media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires

involving this material.

Special protective equipment and precautions for fire-fighters:

As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) Protective Equipment:

and full protective gear.

NFPA Ratings:

NFPA Health: 1 NFPA Flammability: 1 NFPA Reactivity: 0



SECTION 6: ACCIDENTAL RELEASE MEASURES

$\underline{\text{Personal precautions, protective equipment and emergency procedures:}}$

Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use proper personal protective equipment as listed in Section 8. Personal Precautions:

Environmental precautions:

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.

 $\underline{\text{Methods and materials for containment and cleaning up:}}$

Contain spills with an inert absorbent material such as soil or sand. Prevent from spreading by covering, diking or other means. Provide ventilation. Methods for containment:

Clean up spills immediately observing precautions in the protective equipment section. Place into a suitable container for disposal. Provide ventilation. After removal, flush spill area with soap and water Methods for cleanup:

to remove trace residue.

SECTION 7: HANDLING and STORAGE

Euroseal Revision:: 5/23/2019 Product Code: NC-Template

Precautions for safe handling:

Handling: Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing.

Hygiene Practices: Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

Conditions for safe storage, including any incompatibilities:

Storage: Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and

incompatible substances. Keep container tightly closed when not in use.

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE GUIDELINES:

Appropriate engineering controls:

Engineering Controls: Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other

engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance

of the personal protective equipment.

Individual protection measures:

Eye/Face Protection: Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye

and face protection regulation, or the European standard EN 166.

Skin Protection Description: Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be

used to prevent contact with eyes, skin or clothing.

Hand Protection Description: Impervious gloves.

Respiratory Protection: A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be

permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Other Protective: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety

shower

PPE Pictograms:



SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL AND CHEMICAL PROPERTIES:

Physical State: Liquid
Physical State Appearance: Liquid.

Color: Various colors

Odor: Slight latex odor

Odor Threshold: No Data

Boiling Point: 212°F

Melting Point: No Data

Density: 8.8 - 10.0

Specific Gravity: 1.05 - 1.20

Specific Volume: No Data

Solubility: Miscible in water.

Vapor Density: No Data

Vapor Pressure: 17 @ 20 °C/ 68°F Water

Percent Volatile: 74-79

Evaporation Rate: No Data

Evaporation Point: >1

pH: 8.5 - 9.2
Molecular Formula: Mixture

Molecular Weight: Not applicable.

Viscosity: 180 - 240 cP

Coefficient of Water/Oil

Distribution:

No Data

Flammability: No Data
Flash Point: No Data

Euroseal Product Code: NC-Template Revision:: 5/23/2019

Page 3 of 5

Lower Flammable/Explosive Limit: Not applicable. Upper Flammable/Explosive Limit: Not applicable. **Explosive Properties:** Not explosive.

Oxidizing Properties: No Data Refractive Index: No Data

Optical Rotation: Not applicable.

VOC Content: < 250 g/L (less Water)

SECTION 10: STABILITY and REACTIVITY

Chemical Stability:

Chemical Stability: Stable under normal temperatures and pressures.

Possibility of hazardous reactions:

Hazardous Polymerization: Not reported.

Conditions To Avoid:

Conditions to Avoid: Heat, flames, incompatible materials, and freezing or temperatures below 32 deg. F.

Incompatible Materials:

Incompatible Materials: Oxidizing agents. Strong acids and alkalis.

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:

Water:

Ingestion: Oral - Rat LD50 - Lethal dose, 50 percent kill: >90 mL/kg [Details of toxic effects not reported other than lethal dose value] (RTECS)

Alcohols, C9-11, ethoxylated:

Skin:

Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: >2 gm/kg [Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Gastrointestinal - Hypermotility, diarrhea]

(RTECS)

Oral - Rat LD50 - Lethal dose, 50 percent kill: 1378 mg/kg [Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Gastrointestinal - Hypermotility, diarrhea] (RTECS) Ingestion:

Diuron:

Administration onto the skin - Rat LD50 - Lethal dose, 50 percent kill: >5 gm/kg [Details of toxic Skin:

effects not reported other than lethal dose value] (RTECS)

Ingestion: Oral - Rat LD50 - Lethal dose, 50 percent kill: 1017 mg/kg [Behavioral - General anesthetic Behavioral

Oral - Rat LD50 - Lethal dose, 50 percent kill: 1 gm/kg [Details of toxic effects not reported other than

lethal dose value] (RTECS)

Petroleum distillates, solvent dewaxed heavy paraffinic:

Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: >5000 mg/kg [Details of Skin:

toxic effects not reported other than lethal dose value] (RTECS)

Oral - Rat LD50 - Lethal dose, 50 percent kill: >5000 mg/kg [Details of toxic effects not reported other than lethal dose value] (RTECS) Ingestion:

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Ecotoxicity: No ecotoxicity data was found for the product. Environmental Fate: No environmental information found for this product.

SECTION 13: DISPOSAL CONSIDERATIONS

Description of waste:

Consult with the US FPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous Waste Disposal:

waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local

auidelines.

SECTION 14: TRANSPORT INFORMATION

Euroseal Revision:: 5/23/2019 Product Code: NC-Template

DOT Shipping Name: Not restricted as a dangerous good.

DOT UN Number: Not restricted as a dangerous good.

IATA Shipping Name: Not restricted as a dangerous good.

IATA UN Number: Not restricted as a dangerous good.

Canadian Shipping Name: Not restricted as a dangerous good.

Canadian UN Number: Not restricted as a dangerous good.

IMDG UN Number: Not restricted as a dangerous good.

ADR UN Number: Not restricted as a dangerous good.

ADR Shipping Name: Not restricted as a dangerous good.

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product:

California PROP 65: WARNING! This product contains a chemical known to the State of California to cause cancer.

Not restricted as a dangerous good.

Water:

231-791-2 EC Number:

Alcohols, C9-11, ethoxylated:

IMDG Shipping Name:

TSCA Inventory Status: Listed Canada DSL: Listed EC Number: 614-482-0

Diuron:

California PROP 65: Listed in California Prop65 list

330-54-1 EC Number:

 $\underline{Bis(1,2,2,6,6\text{-pentamethyl-4-piperidyl})} sebacate:$

Listed TSCA Inventory Status: Canada DSL: Listed EC Number: 255-437-1

Petroleum distillates, solvent dewaxed heavy paraffinic :

TSCA Inventory Status: Listed Canada DSL: Listed EC Number: 265-169-7

SECTION 16: ADDITIONAL INFORMATION

HMIS Ratings:

HMIS Health Hazard: 1 HMIS Fire Hazard: 1 HMIS Reactivity: HMIS Personal Protection:

Health Hazard	1
Fire Hazard	1
Reactivity	0
Personal Protection	х

SDS Creation Date: July 30, 2015 SDS Revision Date: May 23, 2019

SDS Format:

SDS Author: Actio Corporation

Disclaimer: The information contained herein is, to the best of Stuc-o-flex International, Inc. knowledge, accurate as of the data indicated. Since the information contained herein may be applied under conditions

beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume responsibility for the results of its use. This information is furnished on the condition that the person receiving it shall make his own determination as to the suitability of the material for his particular purpose and on the condition that he assumes the risk of his use thereof.

Copyright© 1996-2018 Enviance. All Rights Reserved.

Euroseal Product Code: NC-Template